

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

SECTION 1. IDENTIFICATION

Product name : ELAN-Guard® EM 59-60MR

Manufacturer or supplier's detailsCompany : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.comE-mail address : Todd.Thomas@altana.comEmergency telephone : INFOTRAC - 1-800-535-5053
number**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : This product is for industrial use only. It is not intended for
consumer use or retail sale.
Refer to Section 15 for any restrictions that may apply**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H361 Suspected of damaging fertility or the unborn child.Precautionary statements : **Prevention:**

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified Epoxy Resin Emulsion

Hazardous components

| Component | CAS-No. | Concentration (%) |
|------------------------|------------|-------------------|
| Epoxy Resin | 25068-38-6 | >= 48 - < 49 |
| Epoxy Resin | 28906-96-9 | >= 4 - < 5 |
| Lewis Acid Accelerator | 34762-90-8 | >= 4 - < 5 |

SECTION 4. FIRST AID MEASURES

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

- | | |
|-------------------------|--|
| General advice | : Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. |
| If inhaled | : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. |
| In case of skin contact | : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Suitable extinguishing media | : Foam Carbon dioxide (CO ₂) Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. |
| Environmental precautions | : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

Absorbent paper or other organic material used for cleaning up resin is a fire hazard, as heat and spontaneous combustion can occur, particularly if the resin was catalyzed. Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
The chemical reaction that cures mixed epoxy is exothermic (heat generating). If left to cure in a contained mass, such as in a mixing vessel, it can generate enough heat to melt plastic, burn skin or ignite surrounding combustible materials. The larger or thicker the epoxy mass, the more heat generated.
Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

Hazardous components without workplace control parameters

Engineering measures : Use with adequate ventilation.
All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Vapour pressure : No data available

Flash point : > 201 °F (> 94 °C)
Method: No information available.
Information taken from reference works and the literature.

Upper explosion limit : No data available

Lower explosion limit : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Relative vapour density : No data available

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

Relative Density/Specific Gravity : No data available
Density : 1.0904 g/cm³ (77 °F (25 °C))

Solubility(ies)
Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Ignition temperature : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 21 mm²/s (104 °F (40 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Conditions to avoid : No data available
Hazardous decomposition products : The by-products expected in incomplete pyrolysis or combustion of epoxy resins are mainly phenolics, CO and water.
chlorinated compounds
Fluorinated hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

Components:**25068-38-6 Epoxy Resin:**

Acute oral toxicity : LD50 (Rat): 11,400 mg/kg

LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
GLP: yes

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): 23,400 mg/kg

LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

Components:**25068-38-6 Epoxy Resin:**

Species: Rabbit

Result: Moderate skin irritation

Species: Rabbit

Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

Serious eye damage/eye irritation**Product:**

Remarks: Causes serious eye irritation.

Components:**25068-38-6 Epoxy Resin:**

Species: Rabbit

Result: Eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**25068-38-6 Epoxy Resin:**

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

Test Type: Mouse Local Lymph Node assay (LLNA)
Species: Mouse
Method: OECD Test Guideline 429
Result: May cause sensitisation by skin contact.
GLP: yes

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Aspiration toxicity**Components:****25068-38-6 Epoxy Resin:**

No aspiration toxicity classification

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Results of PBT and vPvB assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

| | |
|-----------------------------------|---|
| Regulation | 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances |
| Remarks | This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
| Additional ecological information | : No data available |

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : none

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.
Dispose of the solid mass only if cure is complete and the mass has cooled. Follow federal, state or local disposal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

(EPOXY RESIN)
Marine Pollutant : (EPOXY RESIN)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Epoxy resin)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes (Epoxy resin)

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III
Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

ELAN-Guard® EM 59-60MR

Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt)

: Refer to the product technical data sheet for VOC information.

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know


| | |
|------------------------|--------------|
| Epoxy Resin | 25068-38-6 |
| Water | 7732-18-5 |
| Epoxy Resin | 28906-96-9 |
| Lewis Acid Accelerator | 34762-90-8 |
| Modified epoxy | Not Assigned |

New Jersey Right To Know

| | |
|------------------------|--------------|
| Epoxy Resin | 25068-38-6 |
| Water | 7732-18-5 |
| Epoxy Resin | 28906-96-9 |
| Lewis Acid Accelerator | 34762-90-8 |
| Modified epoxy | Not Assigned |

New Jersey Trade Secret Registry Number for the product (NJ TSN) : Not Applicable

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Phenyl glycidyl ether, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All components of this product are listed active and/or are exempt

Section 4 / 12(b) : Not applicable

Section 5 : Not applicable

ELAN-Guard® EM 59-60MR


Version 7

Revision Date 07/22/2021

Print Date 07/22/2021

Section 6

Not applicable

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

| | |
|------------------------|-----------|
| HEALTH | 2* |
| FLAMMABILITY | 1 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 07/22/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.